

ULTIMATE 2560



OConnor introduces the 2575's baby brother...the 2560.

Perfectly suited to the adaptable, a la carte configurations of accessorised digital cinematography. Cameras such as the Alexa in portable configuration or **any lightweight digital cinema camera** (from Sony, Canon, ARRI, AJA, JVC, Panasonic, Vision Research, RED) in 'maxed out' studio configuration. OConnor Ultimate heads have been used on almost every Hollywood movie feature and episodic TV Drama since the early 1990's and OConnor heads in general have been heavily utilised in the industry since 1949.

Continuously adjustable OConnor sinusoidal counterbalance and fluid drag that together give the ultra-smooth characteristic OConnor feel over the largest payload range.

- Cine standard position of controls (including brakes) and front handle mount for intuitive, controlled positioning of camera.
- Lightweight magnesium housing and carbon fiber cover for best in class performance, power to weight ratio and reliability.

Product Specification

Model	1030D	1030DS	2560	2575D	120EX	
Capacity	With +/- 90 degrees tilt	With +/- 90 degrees tilt	With +/- 90 degrees tilt	With +/- 90 degrees tilt	With +/- 90 degrees tilt	With +/- 60 degrees tilt
@ 4 in. (102 mm) [min]	39 lbs. (17.7 kg)	54 lbs. (24.5 kg)	83 lbs. (37.7 kg)	133 lbs. (60.5 kg)	175 lb (79kg)	351 lb (159 kg)
@ 6 in. (152 mm) ± 90°	30 lbs. (13.6 kg)	41 lbs. (18.6 kg)	65 lbs. (29.5 kg)	105 lbs (47.7 kg)	144lb (65kg)	285 lb (129kg)
@ 8 in. (203 mm) ± 80°	24 lbs. (10.9 kg)	33 lbs (14.9 kg)	53 lbs. (24.1 kg)	87 lbs (39.5 kg)	120lb (54kg)	240 lb (108kg)
Platform	Sideload	Sideload	Sideload	Sideload	Sideload	Sideload
Handle(s)	30°	30°	30°	30°	30°	30°
Bases	100mm	100mm	Mitchell, 150 mm	Mitchell, 150 mm	Mitchell	Mitchell
Tilt	+90° / -90°	+60° / -60°	+/- 90 degrees tilt	+90° / -90°	+90° / -90°	+60° / -60°
Height	6.6 in. (16.8 cm)	6.6 in. (16.8 cm)	8 in. (20.3 cm)	8.4 in. (21.3 cm)	9.8 in. (24.8 cm)	9.8 in. (24.8 cm)
Width	7.6 in. (19.3 cm)	7.6 in. (19.3 cm)	11.3 in. (28.7 cm)	12.4 in. (31.5 cm)	13.5 in. (34.3 cm)	13.5 in. (34.3 cm)
Depth	4.6 in. (11.7 cm)	4.6 in. (11.7 cm)	7.5 in. (19.1 cm)	8.6 in. (21.8 cm)	10.5 in. (26.6 cm)	10.5 in. (26.6 cm)
Weight	8.7 lbs. (3.9 kg)	8.7 lbs. (3.9 kg)	16.2 lb. (7.3 kg)	22.9 lbs (10.4 kg)	34.1 lbs (15.5 kg)	34.1 lbs (15.5 kg)

Counterbalance Chart

