

aktiv14T



Level up with aktiv[™] the fluid head built for speed.

When you have just one chance to capture the perfect shot, mount, level and lock the revolutionary aktiv TM fluid head in seconds.

Sachtler's unique SpeedLevel™ and SpeedSwap™ technologies deliver the fastest way to place and position your camera; adjust the level in an instant without ever taking your eye off the action; get closer to the ground than ever before for extreme low-angle shots or swap between a tripod, slider, or hand held without missing a beat. Capture the widest range of shots in the shortest time with aktiv™.

- Level and lock your head in an instant without missing a second of action.
 Unique SpeedLevel[™] technology.
- Visible from any height or angle day or night. Innovative PrismBubble.
- Capture extreme low angle shots right down to the ground.
 Innovative streamlined mounting system.
- Switch between tripod and slider in seconds. Revolutionary SpeedSwapTM system.
- Create moving stories, whatever the weather. Performance tested to the extreme.
- Touch & Go quick release system.
 Simply drop the camera plate into the base the Touch & Go mechanism locks automatically.
 Pull the lever to remove your camera in an instant.

aktiv/47 s2076T

aktiv $^{\text{TM}}$ 14T Touch & Go fluid head with SpeedLevel $^{\text{TM}}$ technology

Bowl size: 100 mm with SpeedSwap™ base **Payload Range:** 0-16 kg / 0 - 35.3 lb

Counterbalance steps: 15+0

Drag setting: 7+0

Weight: 3.4 kg / 7.5 lb **Level:** Illuminated PrismBubble Camera fitting: Touch & Go 16 Sliding range: 70 mm / 2.8 in Tilt range: +90° to -70° Temperature range:

-40°C to +60°C / -40°F to +140°F





Built for Speed.

Level up and lock your head in an instant.

Unique SpeedLevel™ technology

Never miss the shot. aktivTM fluid heads feature revolutionary Speed-LevelTM technology. Release, level, and lock your head tightly into the perfect position without missing a second of action.



Visible from any height or angle - day or night.

Innovative PrismBubble

Clear confirmation that the camera is level comes from the illuminated PrismBubble visible from any height or angle – day or night.



Capture extreme low-angle shots right down to the ground.

Innovative streamlined mounting system

Go lower than ever. $aktiv^{TM}$ and flowtech® combine to provide a flexible one tripod solution delivering the widest height range. With no bowl clamp required, $aktiv^{TM}$ heads allow flowtech® tripods to go flat to the ground for the perfect low-angle shot.



Switch between tripod and slider in seconds.

Revolutionary SpeedSwap™ system.

Stay fast for ultimate creativity. aktivTM fluid heads feature the unique SpeedSwapTM system, allowing lightning-fast camera swaps from a tripod to a slider without missing a beat. The perfect camera movement is just a SpeedSwapTM awau.









System aktiv14T flowtech100 GS

System aktiv14T flowtech100 MS

	320/01-1103	320/01-611/13
Spreader type	Ground spreader	Mid-level spreader
Bowl	100 mm with SpeedSwap™	100 mm with SpeedSwap™
Payload range	0 - 16 kg / 0 - 35.3 lb	0 - 16 kg / 0 - 35.3 lb
Counterbalance steps	15+0	15+0
Drag setting	7+0	7+0
Balance range	70 mm / 2.8 in	70 mm / 2.8 in
Tilt range	+90° to -70°	+90° to -70°
Camera fitting	Touch & Go 16	Touch & Go 16
System weight	7.4 kg / 16.3 lb	7.5 kg / 16.5 lb
Height range with spreader	60 - 176 cm / 23.6 - 69.3 in	71 - 172 cm / 27.9 - 67.7 in
Height range without spreader	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in
Transport length	87 cm / 34.3 in	87 cm / 34.3 in
Tripod stages	2	2
Tripod material	Carbon fibre	Carbon fibre

Combine the world's fastest tripod and the fluid head built for speed to record every second of action without missing a beat. aktiv flowtech systems are the perfect one tripod solution to capture the widest range of shots in the shortest time including extreme low-angle shots, closer to the ground than ever.