



FSB *MkII*



Fluid, Smooth, Balanced

Capture the moment precisely

Redesigned with features from the revolutionary Sachtler aktiv fluid head range, FSB delivers precision movement with finely calibrated levels of drag and counterbalance for the perfect shot. The streamlined profile is built to withstand the toughest conditions to deliver repeatable, reliable camera support shot after shot.

- **Smooth operation.**
Create precision pans with smooth starts and soft stops.
- **Finely balanced.**
Delivering smooth pan-tilt fluid actions to match any camera payload from 0kg.
- **Always on the level.**
Innovative illuminated PrismBubble visible from any height – day or night.
- **Built for endurance**
Engineered to the highest standards with tough materials and precision components.



FSB **6** *MkII*

Payload Range
0 - 8 kg
0-17.6 lb



FSB **8** *MkII*

Payload Range
0 - 12 kg
0 - 26.5 lb

Mid-level spreader systems



**System FSB 6 Mk II
75/2 AL MS
0473AM**

**System FSB 6 Mk II
75/2 CF MS
0473CM**

**System FSB 8 Mk II
75/2 AL MS
0773AM**

**System FSB 8 Mk II
75/2 CF MS
0773CM**

Bowl	75 mm	75 mm	75 mm	75 mm
Payload range	0 - 8 kg / 0-17.6 lb	0 - 8 kg / 0-17.6 lb	0 - 12 kg / 0-26.5 lb	0 - 12 kg / 0-26.5 lb
Counterbalance steps	15+0	15+0	15+0	15+0
Drag setting	3+0	3+0	7+0	7+0
Camera fitting	Sideload S	Sideload S	Sideload S	Sideload S
System weight	5.2 kg / 11.5 lb	4.7 kg / 10.4 lb	5.4 kg / 11.9 lb	4.9 kg / 10.8 lb
Height range	81 - 171 cm / 31.9 - 67.3 in	81 - 171 cm / 31.9 - 67.3 in	81 - 171 cm / 31.9 - 67.3 in	81 - 171 cm / 31.9 - 67.3 in
Transport length	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in

Ground spreader systems



**System FSB 6 Mk II
75/2 AL GS
0471AM**

**System FSB 6 Mk II
75/2 CF GS
0471CM**

**System FSB 8 Mk II
75/2 AL GS
0771AM**

**System FSB 8 Mk II
75/2 CF GS
0771CM**

Bowl	75 mm	75 mm	75 mm	75 mm
Payload range	0 - 8 kg / 0-17.6 lb	0 - 8 kg / 0-17.6 lb	0 - 12 kg / 0-26.5 lb	0 - 12 kg / 0-26.5 lb
Counterbalance steps	15+0	15+0	15+0	15+0
Drag setting	3+0	3+0	7+0	7+0
Camera fitting	Sideload S	Sideload S	Sideload S	Sideload S
System weight	5.4 kg / 11.9 lb	4.9 kg / 10.8 lb	5.6 kg / 12.3 lb	5.0 kg / 11 lb
Height range	59 - 175 cm / 23.2 - 68.9 in	59 - 175 cm / 23.2 - 68.9 in	59 - 175 cm / 23.2 - 68.9 in	59 - 175 cm / 23.2 - 68.9 in
Transport length	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in

Built for endurance.

Engineered to the highest standards with tough materials and precision components, FSB is built for endurance. With no variation in performance in the widest range of temperatures and environments, FSB is the first choice for outdoor operators.

