



System FSB 10 T FT MS

Sachtler System FSB 10 Touch & Go carbon fibre with Fluid Head, flowtech® Tripod, Mid-Level Spreader, Handle & Bag

SKU: S2046FTMS

The Sachtler FSB 10 T Fluid Head is a versatile 100 mm solution for projects that need a light, strong and reliable gear addition. When you need speed as well as high performance, the convenient Touch & Go release plate makes attaching your camera securely as simple as clicking it into place. The camera platform's sliding range of 60 mm and payload of up to 12 kg, supports the majority of today's digital cinemas.

The 100 mm levelling ball makes balancing the fluid head on your tripod fast, while its flat base means you can mount it on any flat surface. Once you are ready to shoot, Sachtler's unique frictionless leak-proof fluid damping, with five horizontal and vertical grades of drag, means that you'll never have uncontrolled jerks or vibrations ruining your tilts and pans. This high level of performance is guaranteed in any environment, including sub-zero shoots, meaning that Sachtler FSB 10 T Fluid Head won't let you down when you need it.

For shoots where you need to balance quick setup, easy transport, support and stability, the Sachtler flowtech® 100 MS Carbon Fibre Tripod is a valuable addition to your gear. The unique design gives each leg individual adjustment while releasing and locking together, meaning setting up on any surface is as easy as releasing a catch. The ergonomic design makes the tripod light and comfortable to carry, no matter where your creativity takes you.

Weighing only 4.1 kg, the Sachtler flowtech® 100 MS can support a payload of up to 30 kg and extend to a maximum height of 155 cm. This versatility and flexibility are matched by high levels of stability so you can be sure that you'll always be able to get the shot you are looking for. When you are ready to move on, the legs all lock together with a single mechanism to save you even more time and energy.

Technical specifications

Feature	Metric	Imperial
Range	FSB	FSB
Weight	6.90 kg	15.18 lb
Temperature range	-40 to 60 °C	-40 to 140 °F
Sliding range	60 mm	2.34 in
Interface Compatibility	Touch & Go	Touch & Go
Bowl size	100 mm	100 mm
Material	Carbon Fibre	Carbon Fibre
Transport length	860 mm	33.54 in
Tripod stages	2	2
Payload	4 to 12 kg	8.80 to 26.40 lb
Tilt range	90° to -75°	90° to -75°
Height with spreader	0.71 to 1.72 m	2.33 to 5.64 ft
Height without spreader	0.41 to 1.70 m	1.34 to 5.58 ft
Spreader type	Mid-level spreader	Mid-level spreader
Pan bar count	1	1
Counterbalance	10 counterbalance steps	10 counterbalance steps
Drag	5 + 0 horizontal and vertical drag settings	5 + 0 horizontal and vertical drag settings

What's in the box?

- **Carry handle flowtech®**
- **FSB 10 T**
- **Tripod flowtech® 100 MS**
- **Padded bag ENG**

Data sheets

